EAST Browser - L15: (6) 13 and (prio... | US 5548108 A | Tag: S | Doc: 5/6 (SORTED) | Format: KWIC

File Edit View Tools Window Help

Detailed Description Text - DETX (28):

The current design of the electronic circuitry of FIG. 6 is intended to have the application processing task 108 be replaceable with other types of processing depending upon the application or type of symbol reader the design is to be used in the application processing task 108 will set the priorities of the other tasks (tasks 160, 104, 112, and 108). Since the application processing task 108 has the capability of setting the task priorities (Step 816, FIG. 8), it also has the capability of altering the priorities according to need. Thus, for example, if a symbology is selected to be read that is so complex as to require sufficient decoding processing time to bottleneck system throughput, then the application processing task can dynamically change the priority (Step 816, FIG. 8) of the label decode task 104 to be the highest priority task for execution, and this task would execute as long as inputs existed for it to decode. Further, if one application using this design requires more (or less) tasks than the current application, then the application processing task 108 can create the number of tasks needed. For example, to have a barcode reader than can simultaneously output to two different output devices, two data output tasks are required, instead of only one.

Details | Text | Image | HTML | KWIC

	U	Document I	Issue D	
3	☐	US 5790536 A	199808 04	Hierarch intelligen
4	☐	US 5936224 A	199908 10	Method symbols operator
5	☐	US 5548108 A	199608 20	Method
6	☑	US 5914481 A	199906 22	Portable input are

Details | Text | Image | HTML



Fig. 6

Details | Text | Image | HTML | Full

EAST Browser - L15: (6) 13 and (prio | US 5548108 | Tag: S | Doc: 5/6 (SORTED) | "Full" 6/15 (Total images 15)
File Edit View Tools Window Help

Detailed Description Text - DETX (28):

The current design of the electronic circui
the application processing task 108 be repl
processing depending upon the application
is to be used in the application processing t
the other tasks (tasks 160, 104, 112, and 1
processing task 108 has the capability of se
816, FIG. 8), it also has the capability of alt
to need. Thus, for example, if a symbology
complex as to require sufficient decoding p
throughput, then the application processing
priority (Step 816, FIG. 8) of the label deco
priority task for execution, and this task wo
existed for it to decode. Further, if one app
requires more (or less) tasks than the curre
application processing task 108 can create
example, to have a barcode reader than ca
different output devices, two data output ta
one.

Details Text Image HTML KWIC

	U	Document I	Issue D	
3	☐	US 5790536 A	199808 04	Hierarch intelligen
4	☐	US 5936224 A	199908 10	Method symbols operator
5	☐	US 5548108 A	199608 20	Method
6	☑	US 5914481 A	199906 22	Portable input are

Details Text Image HTML



Fig. 6

Details Text Image HTML Full

EAST Browser - L10: (15) 9 and camera | JP 2002131811 A | Tag: S | Doc: 4/15 (SORTED) | Format: FULL

File Edit View Tools Window Help

DERWENT-WEEK: 200251

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Camera includes processor which gives high priority for execution of tasks controlled by switch operation

PATENT-ASSIGNEE: CANON KK[CANO]

PRIORITY-DATA: 2000JP-0319399 (October 19, 2000)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
JP 2002131811 A	May 9, 2002	N/A	006	G03B 017/00

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO	APPL-DATE
JP2002131811A	N/A	2000JP-0319399	October 19, 2000

Details | Text | Image | HTML | FULL

	U	Document I	Issue D	
3	□	US 4864511 A	198909 05	Automat
4	□	JP 2002131811 A	200205 09	Camera for execu
5	□	US 5913062 A	199906 15	Conferer local anc providinc
6	☑	US 2002009182	200207 11	Intermed a central

Details | Text | Image | HTML

報 (A) (11)特許出願公開番号
特開2002-131811
(P2002-131811A)
(43)公開日 平成14年5月9日(2002.5.9)

		テーマコード(参考)
G03B 17/00	Q	2H030
H04N 5/225	F	2H051
G03B 7/11	N	5C022

審査請求 未請求 請求項の数 5 OL (全 6 頁)

出願人 000001007
キヤノン株式会社
東京都大田区下丸子3丁目30番2号
発明者 亀山 誠
東京都大田区下丸子3丁目30番2号 キヤノン株式会社内
代理人 100067541
弁理士 岸田 正行 (外3名)
Fターム(参考) 2H030 MB01
2H051 AA01 EA25 EA29 EC02 EC05 EC10
5C022 AB12 AB15 AB17 AB29 AC32 AC52 AC74

(57)【要約】
【課題】リアルタイムOSによってプログラムの実行状態を制御するマイクロプロセッサ搭載のカメラにおける操作に対する応答性とプログラムの生産性を向上させる。
【解決手段】カメラのタスクとして、スイッチ操作による制御を行うタスク（タスク1）、フィルム給送タスク（タスク2）、焦点検出演算を行うタスク（タスク3）の中で、実時間応答性の高い処理を行うタスクの実行優先順位を、実時間応答性の低い処理を行うタスクの実行優先順位よりも高く、すなわち、タスク1の優先順位を最も高く、次いでタスク2、タスク3を最も低い優先順位とした。



Details | Text | Image | HTML | Full

EAST Browser - [15: (6) 13 and (prio | US 5936224 A | Tag: S.T1 | Doc: 4/6 (SORTED) | Format: KWIC
File Edit View Tools Window Help

Detailed Description Text - DETX (43):

In step 310, the CPU 14 selects one of the contours determined under steps 302-308, and determines an orientation of the symbol image within the stored image. Under step 310, the CPU 14 can employ some of the same techniques employed under step 114. For example, the CPU 14 can select the first contour to be fully identified under one of the steps 302-308. Alternatively, the CPU can select the contour produced by the highest priority task in the finding set of modules 301. Based on the selected contour, the CPU 14 determines an orientation of the symbol image within the stored image by performing various techniques, such as those described in the patents and applications listed above with respect to the set of finding modules 301.

Current US Original Classification - CCOR (1):

235/462.1

Details | Text | Image | HTML | KWIC



	U	Document I	Issue D	
2		US 5895906 A	199904 20	Hand-he module a
3		US 5790536 A	199808 04	Hierarch intelligen
4		US 5936224 A	199908 10	Method symbols operator
5		US 5548108 A	199608 20	Method

Details | Text | Image | HTML



Fig. 2

Details | Text | Image | HTML | Full

EAST Browser - L10: (15) 9 and camera | US 4932826 A | Tag: S | Doc: 1/15 (SORTED) | Format: KWIC
File Edit View Tools Window Help

Detailed Description Text - DETX (23):

The channel side control processor 323, also known as channel processor, is a complete microprocessor that controls all activity on the channel side of the TCU 111. In a presently preferred embodiment of the invention, it consists of a high power, 16-bit micorprocessor chip, with associated EPROM and RAM memories, clocks, interrupt handlers, registers, and parity generators and checkers. As such, the channel processor 323 is a multi-tasking, interrupt-driven processor. It responds immediately to tasks with a high priority than the task it is processing and stores a program address in memory, so that it can return to the previous job where it left off.

Detailed Description Text - DETX (96):

Having described the LMU 106 in some detail, the following will explain the requirements for interfaces within the LSM 108, the LMU 106, its associated software, and operating procedures. As explained herein above, the REI 156 is the communications path between the LCU 109 and the electronics which are

Details | Text | Image | HTML | KWIC

	U	Document I	Issue D	
1	☐	US 4932826 A	199006 12	Automat
2	☐	US 4928245 A	199005 22	Automat
3	☐	US 4864511 A	198909 05	Automat
4	☐	JP 2002131811	200205 09	Camera for execu

Details | Text | Image | HTML



Fig. 16

Details | Text | Image | HTML | Full

EAST Browser - L31: (34) (PLD or prog...) | US 6489992 B2 | Tag: S | Doc: 14/34 (SORTED) | Format: KWIC

File Edit View Tools Window Help

---------- KWIC ---------- Official Notice

Detailed Description Text - DETX (112):

Referring back to FIG. 1, the timing controller 22 provides overall timing control of the A/D, the analog signal processor, and the CCD imager to synchronize image acquisition and signal processing. One example timing controller in accordance with the invention consists of a programmable logic device that embodies a control state machine for synchronizing image integration, image signal readout, analog processing, A/D conversion, image frame sequence formatting, and digital image processing.

Details | Text | Image | HTML | KWIC

	U	Document I	Issue D	
13	☐	US 6473062 B1	200210 29	Intelliger
14	☐	US 6489992 B2	200212 03	Large fie
15	☐	US 2001001936 1 A1	200109 06	Low-light
16	☑	US 5880777 A	199903 09	Low-light

Details | Text | Image | HTML



Details | Text | Image | HTML | Full

EAST Browser - L36: (5) 35 same expo... | US 5247366 A | Tag: S | Doc: 1/5 (SORTED) | Format: KWIC
File Edit View Tools Window Help

Detailed Description Text - DETX (30):

Elements 125, 130, 132, 133, 134, 136, 138, 140 of FIG. 10 are substantially similar to corresponding elements shown in FIG. 9. However, exposure-dependent look-up table 142 is added downstream of the intersection of neighborhood processing block 132 and the R, G and B components of the images. Exposure-dependent look-up table 142 includes a first look-up table (LUT1) which operates on the long-exposure image. A typical function implemented by LUT1 is LUT1(I)=5 * I.sup.0.6. Likewise, exposure-dependent look-up table 142 includes a second look-up table (LUT2) which operates on the short-exposure image. A typical function implemented by LUT2 is LUT(I)=I.sup.1.1. The use of the exposure-dependent look-up table 142 thereby enhances the dynamic range (histogram) of the bright area, thus improving the contrast and compensating for the loss of the saturation of the color in the bright areas which is due to the addition of background DC level from the long exposure frame. Moreover, LUT1 and LUT2 can be modified so as to include the gain factor, thereby allowing the three by three convolution kernel of neighborhood processing block 132 to be simplified to include a central element of epsilon (.epsilon.) and eight peripheral elements of negative one eighth (-1/8).

Details | Text | Image | HTML | KWIC



US005247366A

Patent Number: 5,247,366

Date of Patent: Sep. 21, 1993

OTHER PUBLICATIONS

ABSTRACT

Claims, 10 Drawing Sheets

	U	Document I	Issue D	
1		US 5247366 A	199309 21	Color wi
2		US 5767993 A	199806 16	Holograp
3		US 2002003913 7 A1	200204 04	Methods control
4		US 5124913 A	199206 23	Rule-bas final scal

Details | Text | Image | HTML



Details | Text | Image | HTML | Full

EAST Browser - L30: (51) (multitask$3 ...) | US 20020041761 A1 | Tag: S | Doc: 17/61 (SORTED) | Format: KWIC
File Edit View Tools Window Help

Detail Description Paragraph - DETX (14):

[0024] DSC systems may be even more versatile with the ability to annotate images with text/speech. The preferred embodiment programmable DSP allows easy inclusion of a modem and/or a TCP/IP interface for direct connection to the Internet. DSCs may run complex multi-tasking operating systems to schedule the various real-time tasks.

Detail Description Paragraph - DETX (18):

[0028] (1) Preview mode has data flow as illustrated in FIG. 2. ARM 130 sets CCD 150 into high-frame-rate readout mode (reduced vertical resolution). ARM 130 enables preview engine 104 and sets the appropriate registers for the default parameters. The raw CCD data is streamed into preview engine 104 and, after preview engine processing, is streamed into SDRAM 160. ARM 130 enables TV encoder 106 to display the preview engine output. Preview engine 104 processing (hardware) includes gain control, white balance, CFA interpolation, down-sampling, gamma correction, and RGB to YUV conversion. ARM 130 commands DSP 122 to perform auto exposure and auto white balance whenever required. DSP 122 processing includes auto exposure, auto white balance, and auto focus. ARM

Details | Text | Image | HTML | KWIC



	U	Document I	Issue D	
15		US 6438594 B1	200208 20	Deliverin interface
16		US 2002013568 3 A1	200209 26	Digital st
17		US 2002004176 1 A1	200204 11	Digital st
18		US 2002002760	200203 07	Digital st

Details | Text | Image | HTML | Full

EAST Browser - L30: (61) (multitask$3 ... | US 20020012055 A1 | Tag: S | Doc: 21/61 (SORTED) | Format: KWIC

File Edit View Tools Window Help

Detail Description Paragraph - DETX (14):

[0047] DSC systems may be even more versatile with the ability to annotate images with text/speech. The preferred embodiment programmable DSP allows easy inclusion of a modem and/or a TCP/IP interface for direct connection to the Internet. DSCs may run complex multi-tasking operating systems to schedule the various real-time tasks.

Detail Description Paragraph - DETX (19):

[0052] (1) Preview mode has data flow as illustrated in FIG. 2. ARM 130 sets CCD 150 into high-frame-rate readout mode (reduced vertical resolution). ARM 130 enables preview engine 104 and sets the appropriate registers for the default parameters. The raw CCD data is streamed into preview engine 104 and, after preview engine processing, is streamed into SDRAM 160. ARM 130 enables TV encoder 106 to display the preview engine output. Preview engine 104 processing (hardware) includes gain control, white balance, CFA interpolation, down-sampling, gamma correction, and RGB to YUV conversion. ARM 130 commands DSP 122 to perform auto exposure and auto white balance whenever required. DSP

Details | Text | Image | HTML | KWIC

	U	Document I	Issue D	
19	☐	US 2002001544 7 A1	200202 07	Digital st
20	☐	US 2002001239 8 A1	200201 31	Digital st
21	☐	US 2002001205 5 A1	200201 31	Digital st
22	☑	US 2002001205	200201 31	Digital st

Details | Text | Image | HTML



FIG. 1b

Details | Text | Image | HTML | Full

EAST Browser - L30: (61) (multitask$3 | US 20020135683 A1 | Tag: S | Doc: 16/61 (SORTED) | Format: KWIC

File Edit View Tools Window Help

Detail Description Paragraph - DETX (14):

[0046] DSC systems may be even more versatile with the ability to annotate images with text/speech. The preferred embodiment programmable DSP allows easy inclusion of a modem and/or a TCP/IP interface for direct connection to the Internet. DSCs may run complex multi-tasking operating systems to schedule the various real-time tasks.

Detail Description Paragraph - DETX (19):

[0051] (1) Preview mode has data flow as illustrated in FIG. 2. ARM 130 sets CCD 150 into high-frame-rate readout mode (reduced vertical resolution). ARM 130 enables preview engine 104 and sets the appropriate registers for the default parameters. The raw CCD data is streamed into preview engine 104 and, after preview engine processing, is streamed into SDRAM 160. ARM 130 enables TV encoder 106 to display the preview engine output. Preview engine 104 processing (hardware) includes gain control, white balance, CFA interpolation, down-sampling, gamma correction, and RGB to YUV conversion. ARM 130 commands DSP 122 to perform auto exposure and auto white balance whenever required. DSP 122 processing includes auto exposure, auto white balance, and auto focus. ARM

Details | Text | Image | HTML | KWIC

	U	Document I	Issue D	
14	☐	US 5946667 A	199908 31	Data pro instrume
15	☐	US 6438594 B1	200208 20	Deliverin interface
16	☐	US 2002013568 3 A1	200209 26	Digital st
17	☑	US 2002004176	200204 11	Digital st

Details | Text | Image | HTML



US 20020135683A1

(19) Pub. No.: US 2002/0135683 A1
(43) Pub. Date: Sep. 26, 2002

Related U.S. Application Data

Provisional application No. 60/172,760, filed on Dec. 20, 1999. Provisional application No. 60/176,272, filed on Jan. 14, 2000. Provisional application No. 60/177,432, filed on Jan. 21, 2000. Provisional application No. 60/214,951, filed on Jun. 29, 2000. Provisional application No. 60/215,000, filed on Jun. 29, 2000.

Publication Classification

Int. Cl.[7] H04N 5/235; H04N 5/232
U.S. Cl. 348/223; 348/362; 348/221; 348/346

ABSTRACT

...ne-scaling is a digital image with pixel intensities ...ated by a linear combination of pixel intensities and ...ulative intensity distribution values.



Details | Text | Image | HTML | Full

EAST Browser - L33: (2) 32 with product | US 4762998 A | Tag: S | Doc: 1/2 (SORTED) | Format: KWIC
File Edit View Tools Window Help

FIG. 16 shows the relative DC signal (called "gain") as a function of the scanning exposure .eta. and the ratio k of spot size .sigma. to raster pitch p. The plateau in FIG. 16 represents the region of operating parameters wherein the phosphor is fully discharged. Thus, according to the first aspect of the present invention operating parameters are employed that insure operation on this plateau. As seen from FIG. 16, the exposure required to saturate the gain decreases as the spot size increases, for a given raster pitch. However, as spot size is increased, frequency response decreases. FIG. 17 shows the product of the gain and the slow-scan MTF at a fixed frequency .nu..sub.y, for a circularly symmetric gaussian beam. From FIG. 17 it is seen that as k (.sigma..sub.y /p) is increased for a given exposure, the gain-MTF product (contrast transfer function CTF) at first increases because of the increase in gain. Then the product decreases because of the loss in spatial resolution. Thus, there is an optimal ratio k (in the sense of maximizing the system CTF) in the range of 0.2 to 0.3 depending upon the scan exposure .eta.. Thus, according to a preferred mode of practicing the present invention, for a raster scanned read out with a gaussian shaped beam, the value of k (.sigma..sub.y /p) is between 0.2 and 0.3.



FIG. 16



FIG. 17

	U	Document I	Issue D	
1	☐	US 4762998 A	198808 09	Method transpar
2	☐	US 2002003913 7 A1	200204 04	Methods

EAST Browser - L32: (50) contrast.wt | US 20020054697 A1 | Tag: S | Doc 5/50 (SORTED) | Format: KWIC
File Edit View Tools Window Help

embodiments. However, in the fourth embodiment, the radiological image is acquired on a low-contrast but wide-latitude mammographic film 600. This embodiment and the third embodiment differ in the source of the digitized image 40. The acquisition system, in this example, uses a relatively inexpensive conventional mammographic intensifying screen cassette 620. The cost ratio between this screen cassette 620 and a typical current digital mammographic system can be several orders of magnitude, e.g., approximately 1000 times. The standard screen-film acquisition and exposure technique and the conventional mammographic x-ray system (not shown here) will be unchanged for use in this embodiment. The high voltage of the x-ray generator typically is in the range of 25 to 35 KVp (kilovolt peak) or, as discussed below, can be raised to a level in the 40 to 55 KVp range. By reducing the average contrast gradient G of the mammographic film 600 say from about 3.0 to about 2.0, or to 1.5 or even less, we pick up substantial gain in exposure latitude.

Details | Text | Image | HTML | KWIC

US 20020054697A1

(10) Pub. No.: US 2002/0054697 A1
(43) Pub. Date: May 9, 2002

ABSTRACT

x-ray system acquires an initial low-contrast, wide (G=2.5, or G=2 or less) x-ray image of a breast. A ...ssing system automatically finds suspected abnormali... in the breast by processing the low contrast initial image, ...then automatically converts the initial x-ray image to a ...contrast, narrow latitude image at the locations of the ...d abnormalities to thereby facilitate diagnosis and ...nt care. The technology includes effective ways to ...ture, process and display the various images, and can be ...plied to other types of images.

	U	Document I	Issue D	
3	□	US 5049916 A	199109 17	Automati paramete extra sys
4	□	US 5792601 A	199808 11	Composi preparati
5	□	US 2002005469 7 A1	200205 09	Compute
6	☑	US 2001003368	200110 25	Compute

Details | Text | Image | HTML



Details | Text | Image | HTML | Full

EAST Browser - L35: (5) 35 same expo. | US 20010008419 A1 | Tag: S | Doc: 5/5 (SORTED) | Format: KWIC
File Edit View Tools Window Help

Detail Description Paragraph - DETX (37):

[0048] A gradation correcting section 8 corrects the gradation of the mixed signal in such a manner that contrast of the gradation is emphasized when the histogram frequency of an image is large. A main signal processing signal 11 receives a gradation corrected signal produced from the gradation correcting section 8. An average brightness detecting section 9 detects an average brightness value based on the mixed signal. The microcomputer 10 inputs the average brightness value detected by the average brightness detecting section 9. The microcomputer 10 compares the detected average brightness value with a predetermined target brightness value. When the detected average brightness value is lower than the target brightness value, the microcomputer controls the AGC section 3 to increase the gain for the long-term exposure signal, thereby increasing the level of a video signal. On the other hand, when the detected average brightness value is higher than the target brightness value, the microcomputer controls the AGC section 3 to decrease the gain of AGC section 3, thereby decreasing the level of a video signal. In this manner, to control the level of a video signal, the microcomputer calculates an optimum gain to be set in the AGC section 3 and controls the gain of the AGC section 3 to the calculated value.

Details | Text | Image | HTML | KWIC



	U	Document I	Issue D	
3	☐	US 20020039137 A1	20020404	Methods control
4	☐	US 5124913 A	19920623	Rule-bas final scal
5	☐	US 20010008419 A1	20010719	Solid sta

Details | Text | Image | HTML | Full

EAST Browser - L31: (34) (PLD or prog... | US 6473062 B1 | Tag: S | Doc: 13/34 (SORTED) | Format: KWIC
File Edit View Tools Window Help

the signal synchronously at the pixel rate 25. The digital signal that is representative of the detected intensity of the light that is imaged from the illuminated object is applied to a digital signal processor (DSP), micro-controller or microprocessor that usually processes the images acquired, hereinafter referred to as processor 52. Processor 52 has the necessary memory resources, I/O and computing capabilities to handle the interface and algorithms described herein. The digitizing performed by ADC 50 and the processing performed by processor 52 can be deported to separate calibration or processing equipment, if the system does not require standalone calibration or sophisticated processing. The processor 52 controls all of the calibration steps as described herein. The values of the corrected intensity matrix 46 are calculated in processor 52. These values are then converted per FIG. 14 and loaded in the programmable light source sequencer 56. The light source sequencer is a logic device that has: either ISP (In Situ Programming) capability, such as a CPLD (Complex Programmable Logic Device), or FPGA (Field Programmable Gate Array) using Flash, E.sup.2 or RAM based technology, or any equivalent capability that allows full programming of a individual pulse width control on many outputs,

Details | Text | Image | HTML | KWIC

US006473062B1

(10) Patent No.: US 6,473,062 B1
(45) Date of Patent: Oct. 29, 2002

ABSTRACT

...board is a intelligent light source that is capable of ...ding a uniform illumination image across the surface of ...luminated object analyzed by an optical detector. This is ...complished by individually controlling each light-...ting element of a linear array of light elements. Cali-...tion of the array is accomplished by sequentially illumi-...ng each optical element of the source and building an ...y of normalized detected data. The matrix is then ...ored and multiplied by a linear array of ones to generate ...calibration data. The calibration data are then used to ...gram a simple logic device that allows accurate digital ...rol of the intensity of each individual light element.

5 Claims, 11 Drawing Sheets



	U	Document I	Issue D	
11	□	US 6371672 B1	200204 16	Imager f interface customiz
12	□	US 2003014465 0 A1	200307 31	Integrate photoabl
13	□	US 6473062 B1	200210 29	Intelliger
14	□	US 6489992 B2	200212 03	Large fie

Details | Text | Image | HTML
Details | Text | Image | HTML | Full

EAST Browser - L31: (34) (PLD or prog...) | US 6371672 B1 | Teq: S | Doc: 11/34 (SORTED) | Format: KWIC
File Edit View Tools Window Help

Detailed Description Text - DETX (52):

In one embodiment, the flash memory 1112 includes a direct memory access. The customized rasterizer board 312 may also be a high density board having multiple tracing layers for providing a modularized imager design. The customized programmable logic device (CPLD) 1108 formats data for the one or more pen driver boards 1200 (FIG. 9), and provides a data pathway between the microprocessor 1106 and the one or more pen driver boards 1200 (FIG. 9). Embodiments are also envisioned in which the customized programmable logic device (CPLD) 1108 is also used as a high speed device for quickly processing the imaging data, and converting it into a bitmap. The customized programmable logic device (CPLD) 1108 is specifically design to process information 1000 times faster than if a microprocessor-based architecture were used. Embodiments are also envisioned wherein the customized programmable logic device (CPLD) 1108 may also include either a programmable logic array (PLA), a programmable array logic (PAL), a field-programmable gate array (FPGA), a programmable logic device (PLD), or a combination thereof, to provide similar processing speeds.

b

sterizer Printed Circuit Board)

Details | Text | Image | HTML | KWIC

	U	Document I	Issue D	
9		JP 2002290787 A	200210 04	IMAGE F
10		US 5802203 A	199809 01	Image se
11		US 6371672 B1	200204 16	Imager f interface customiz
12		US 2003014465	200307 31	Integrate photoabl

Details | Text | Image | HTML



FIG. 6B

Details | Text | Image | HTML | Full

EAST Browser - L16: (40) (multitask$3... | JP 63101867 A | Tag: S | Doc: 11/40 (SORTED) | Format : FULL

File Edit View Tools Window Help

ABSTRACT:

PURPOSE: To improve the function of a controller, and to reduce its cost by integrating an exposure scan control unit of a copying machine, an AC system control unit, and a main input/output control function, to one controller.

CONSTITUTION: An I/O control circuit 30 is integrally constituted of an exposure scan control unit, an AC system control unit and a main input/output control function. In this way, a circuit board 30 executes i) a positioning control for executing the constant-speed control of a scanner driving servomotor 58 of a variable exposure scanning system and the position control of a mirror driving motor 56, ii) an AC system control for executing the light quantity control of an exposing lamp 61, the temperature control of fixing heaters 62, 63 and the ON/OFF control of a main driving motor 64, iii) a developing bias voltage control, and iv) an I/O control except a copying sequence which is executed by a system control circuit 10, etc. In this way, by providing the circuit 30 for processing in parallel the management of an input/output data to other sequence than the copying sequence, by a multi-task, the arrangement and racking of a wire harness are simplified, the assembling work is executed efficiently, and the cost can be reduced.

COPYRIGHT: (C)1988,JPO&Japio

Details | Text | Image | HTML | FULL



	U	1	Document ID	Issue Date	
10			US 20040042829 A1	20040304	Compact by belt
11			JP 63101867 A	19880506	CONTRO
12			US 6160982 A	20001212	Copy she

EAST Browser - L8: (5) 7 same (came... | US 20040051785 A1 | Tag: S | Doc: 3/5 (SORTED) | Format : KWIC
File Edit View Tools Window Help

DOCUMENT-IDENTIFIER: US 20040051785 A1

TITLE: Electronic camera having a communication function

——— KWIC ———

Detail Description Paragraph - DETX (16):

[0050] FIG. 5 is a flow chart of procedures used by the electronic still camera of the embodiment of the present invention. In this flow chart, for the convenience of explanation, both flow of the photography mode and the communication mode are described. However, for normal control by a microprocessor, a multitask OS (Operating System) method, for example, is generally adopted. In that case, the tasks for the photography mode and the tasks for controlling communication, etc., can be executed in parallel.

Details | Text | Image | HTML | KWIC

	U	1	Document ID	Issue Date	
2	☐	☐	EP 424803 A	19910502	Digitally c holding di text inforr
3	☐	☐	US 20040051785 A1	20040318	Electronic
4			US 5133024 A	19920721	Image da



FIG. 11

EAST Browser - L16: (40) (multitask)$3... | US 6525875 B1 | Tag: S | Doc: 29/40 (SORTED) | Format : KWIC
File Edit View Tools Window Help

by the CCD sensor. This procedure always carries out the same cycle beginning with the voltage 0 and ending with the voltage Umax. The waiting time after the application of a zero voltage to the piezoelectric enables the latter to become stabilized. The waiting time before the start of the acquisition avoids the acquisition of a frame which may have been exposed before the application of the desired exposure conditions. The end of the exposure of an image is indicated on the acquisition cards by the start of the transfer of the corresponding image. The use of an exposure time shorter than the image transfer time prevents the image from being affected by transient states. Giving the process maximum priority prevents the disturbance of acquisition by other system tasks under a multitask operating system. The six images are acquired successively and in real time (no image lost) by the acquisition card in order to minimize the time during which vibrations can affect the result. Each image has the horizontal dimension of hpix and vertical dimension of vpix. During acquisition, images are transferred automatically by the acquisition card into an array which is reserved for them in the computer's central memory. Following the acquisition procedure, there is a resulting array I[a,b,i,j], the index a corresponding to the phase difference, the index b corresponding to the image (phase-shifted or not phase-shifted), the indices i and j being the coordinates in pixels and varying respectively from 0 to hpix-1 and from 0 to vpix-1.

Details Text Image HTML KWIC



Fig.11

	U	1	Document ID	Issue Date	
28			US 20020039137 A1	20020404	Methods
29			US 6525875 B1	20030225	Microsco object an
30			US 6185399 B1	20010206	Multicolor charge ar

EAST Browser - L15: (65) (multitask$3... | US 20030210898 A1 | Tag: S | Doc: 31/65 (SORTED) | Format: KWIC
File Edit View Tools Window Help

to be output to an A/D conversion unit 22. The A/D conversion unit 22 converts the image signal provided by the image-capturing element 21, which is an analog signal, to a digital signal. The signal processing unit 23 implements exposure control of the image-capturing element 21 (e.g., aperture or auto-gain control), and also executes processing such as white balance correction, gamma correction and the like on the image signal provided by the A/D conversion unit 22 to be output to a frame memory 24.

Detail Description Paragraph - DETX (153):

[0259] Next, the camera window or disk window initialization processing implemented in step S221 in FIG. 27 is explained. It is to be noted that the camera window initialization processing and the disk window initialization processing can be executed simultaneously through multitasking. FIG. 35 is a flowchart illustrating the initialization processing for the camera window. First, in step S51, a decision is made as to whether or not the photographing mode is set to ON, and if it is decided that the photographing mode is not set to ON, the operation proceeds to step S252 in which the control unit 34 implements control on the display image generating unit 33 to display the camera icon 51 before ending the processing.

FIG.27



Details | Text | Image | HTML | KWIC

	U		Document ID	Issue Date	
30			US 6549949 B1	20030415	Fixed forr environm
31			US 20030210898 A1	20031113	Image rec dynamic i apparatus methods program
32			US 6434568 B1	20020813	Informatic

EAST Browser - L8: (5) 7 same (came... | US 5744322 A | Tag: S | Doc: 1/5 (SORTED) | Format: KWIC

File Edit View Tools Window Help

apparatus 40 includes an incubator enclosure 42, which has mounted on it an enclosure 44 for the imaging system, a shelf 46 adapted for supporting holders which are to be inserted into the incubator enclosure, an enclosure 48 for an input mechanism 50 (seen in FIG. 8) for introducing holders on the shelf 46 into the incubator enclosure 42, and a hopper 52 for receiving holders that have been ejected from the incubator enclosure. An alternative input means, not illustrated, includes a cartridge capable of containing a plurality of holders in a stack. Such a cartridge may be attached or fitted to the input mechanism in order to transfer holders from the cartridge into the incubator enclosure. A microprocessor 53 is connected to the mechanisms within the incubator enclosure 42. With multi-tasking, the microprocessor can provide several control functions, serving as a control means for the mechanisms which move and queue the holders within the incubator enclosure, as a way of controlling the timing of the taking of images by the camera, and as the counting means. The above referenced U.S. patent application Ser. No. 08/061,678, METHOD FOR THE EARLY DETECTION OF COLONY GROWTH, now U.S. Pat. No. 5,510,246, describes programming suitable for detecting and enumerating microbial colonies; the programming required to control the holder positioning means and the timing of the taking of video images depends on the user interface desired and on the exact physical arrangements and sizing of components, but the expedients required are well known to those of ordinary skill in the programming art.

Details | Text | Image | HTML | KWIC

	U		Document ID	Issue Date	
1			US 5744322 A	19980428	Automate microorg
2			EP 424803 A	19910502	Digitally c holding di text infor
3			US 20040051785 A1	20040318	Electronic

US005744322A

Patent [19]

[11] Patent Number: 5,744,322

[45] Date of Patent: Apr. 28, 1998

...UBATING AND IMAGING
...ISPOSABLE
...M CULTURING DEVICE
...USE

...Krejcarek, White Bear; ...Mach, Shorewood; Scott D. ...Cottage Grove; Thomas A. ...Pfaley, all of Minn.

...n Mining and ...turing Company, St. Paul.

...291

...18, 1994

.../US94/14515

...29, 1996

...29, 1996

...95/16768

...23, 1996

...Application Data

...Ser. No. 168,681, Dec. 17, 1993,

...C12Q 1/06; C12M 1/34

...435/39; 435/286.2; 435/287.3; 435/288.7; 435/303.1; 435/809

...435/29, 30, 34, 40, 285.2, 287.3, 287.9, 288.3, 305.1, 808, 809, 303.1; 422/63, 40/649, 653; 414/222; 382/128, 133

...ces Cited

U.S. PATENT DOCUMENTS

822,354	6/1906	Deacon	40/649
1,768,715	7/1930	Bopp et al.	40/649
3,493,772	2/1970	Deighton, II et al.	250/222
3,736,432	5/1973	Sweet	250/222 PC
3,764,480	10/1973	Jeklin et al.	195/103.5 R
3,811,036	5/1974	Perry	235/92 PC
3,972,778	8/1976	Cenkajlean	195/139

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0 088 621	9/1983	European Pat. Off.	G01N 35/04
0 301 800	2/1990	European Pat. Off.	G01N 35/00
0 397 256	11/1990	European Pat. Off.	G01N 35/00
0 429 030	7/1991	European Pat. Off.	B01L 3/00
0 547 702	10/1993	European Pat. Off.	G01N 35/00
2 632 074	1/1989	France	G06F 15/42
24 43 410 C3	10/1981	Germany	G06M 11/02
39 15806	11/1989	Germany	C12Q 1/06
57-63452	4/1982	Japan	G01N 33/48
2-6729	1/1990	Japan	G01N 15/14
1434465	10/1988	U.S.S.R.	G06M 11/02
2 227 346	7/1990	United Kingdom	G06K 9/03
94/26826	11/1994	WIPO	C12Q 1/04

OTHER PUBLICATIONS

"Count Up to 1000 Objects In A Field, Automatically", by Artek Systems Corporation (3 pages) no date provided.
"Electronic Colony Counters" by VSMF (3 pages) no date provided.

Primary Examiner—William H. Beisner

[57] ABSTRACT

An apparatus for counting microorganism colonies on at least on disposable microorganism culturing medium having a substantially planar substrate. The apparatus has an imaging system for detecting colonies on the substantially planar substrate, and a holder positioning device for storing and ejecting one or more holders, each adapted to support one of the substrates. The positioning device moves the holders sequentially into a predetermined position relative to the imaging system so that images can be obtained. The imaging system cooperates with a counting device for counting the colonies using information from several images provided by the imaging system taken at different times as the positioning device cycles the holders past the predetermined location to be imaged. Suitable holders, and a method of querying and counting colonies on substrates, are also disclosed.

9 Claims, 10 Drawing Sheets



EAST Browser - L18: (201) bar near2 re... | US 5227614 A | Tag: S | Doc: 28/201 (SORTED) | Format: KWIC

File Edit View Tools Window Help

Abstract Text - ABTX (1):

A hand-held processing system wherein a peripheral module may receive therein a computer processor basic module of standardized construction, with a user-immune real-time multi-tasking operating system. Advantageously the peripheral module or computer processor module may include a touch screen or other highly versatile and compact data input/output device adaptable to graphical and/or other input/output modes suitable for different applications, languages and the like.

Brief Summary Text - BSTX (7):

In a preferred embodiment the standardized computer processor module is provided with a multi-tasking operating system such that battery monitoring software and diagnostic routines will run at a fixed priority level at all times while a wide range of applications software can be run concurrently without jeopardizing the reliability of the system under extended portable operating conditions.

Brief Summary Text - BSTX (11):

The computer processor module may be employed with peripheral devices such as printers, laser bar code readers, RF modules, smart card interface modules,

Details | Text | Image | HTML | KWIC

	U	Document ID	Issue Dat	Tit
26		US 5679948 A	1997102 1	Constant luminescence source mc
27		US 5644728 A	1997070 1	Control systems
28		US 5227614 A	1993071 3	Core computer processor module assembled to form a pocket size c
29		US 5483049 A	1996010 9	Coupon exchanging and check wri



FIG. 4

EAST Browser - L19: (32) bar near2 re... | US 5671374 A | Tag: S | Doc: 15/32 (SORTED) | Format: KWIC
File Edit View Tools Window Help

presently commercially available, and the decoding software in these devices can be adapted to the requirements of the PCMCIA defined PC card and ported to the particular circuitry used on the PC card. The details of the commercially available wand based barcode reading software is hereby incorporated by reference.

Detailed Description Text - DETX (135):

In the embodiment of FIG. 26, the adapter chip receives an interrupt from the decoder chip 538 via line 573 each time an character has been decoded and is ready for pickup. The adapter chip 536 then picks up the character and generates an IRQ interrupt to the host on line 574. A program 519 stored on the host computer controls operations of a microprocessor 516 in the host 500 to execute an interrupt service routine to retrieve the character from the adapter chip and place it in the keyboard buffer of the host. An exemplary program to perform the function of program block 519 is included herewith at Appendix A. This program is written in C++ and can be ported to any host with a suitable compiler. Alternatively, the program 519 could transmit the character to another application running on a multitasking host computer. In alternative embodiments, the program 519 can control the microprocessor to move the decoded character or message from the adapter chip 536 into the memory space shared between the PC card and the host.

Details | Text | Image | HTML | KWIC

	U	1	Document ID	Issue Date	
14			US 5845150 A	19981201	Modular c redundan source d
15			US 5671374 A	19970923	PCMCIA scanning computer
16			US 6536670 B1	20030325	PCMCIA barcode



FIG. 26

EAST Browser - L19: (32) bar near2 re... | US 20020039457 A1 | Tag: S | Doc: 13/32 (SORTED) | Format: KWIC

File Edit View Tools Window Help

Summary of Invention Paragraph - BSTX (9):

[0008] A desired imaging device would incorporate a single main processor that would be capable of running the operating system and application program as well as executing the capture and decode program for the image data. An imaging device that has a single processor capable of all of these operations provides a more streamlined and efficient apparatus, and may also use less expensive components. By eliminating from the overall imaging device architecture the need to incorporate a second processor and, in most instances, an associated PCB, the end-user will typically benefit from being provided a device that costs less, is more reliable and less complex. Thus, the invention teaches how to combine the heretofore separate and independent operations mandating multiple microprocessors' memories and transfer interfaces into a single processor capable of multiple operations. Such a combination is not merely the natural consequence of improvements in microprocessor capacity and capabilities because of the necessity to combine separate hardware, software and protocols into a single processor design. The invention teaches how to accomplish all of these disparate tasks with a central processor, and do so in a multi-tasking environment that was not present when using the prior art technique of employing a dedicated (single task) processor to execute the image capture and decode functions.

Details | Text | Image | HTML | KWIC

	U	1	Document ID	Issue Date	
12			US 5761529 A	19980602	Method fo having plu identificat
13			US 20020039457 A1	20020404	Methods centralize
14			US 5845150 A	19981201	Modular c redundan

US 20020039457A1

tes

blication Publication (10) Pub. No.: US 2002/0039457 A1

(43) Pub. Date: Apr. 4, 2002

APPARATUS FOR IMAGE ECODING IN A ROCESSING UNIT

Helms, Monroe, NC (US); . Dobeck, Matthews, NC (US); D. Harper, Charlotte, NC (US)

LLP CA PLAZA N STREET, SUITE 4000 28280-4000 (US)

eld Products, Inc.

033,148

b 17, 2001

Application Data

provisional application No. Sep. 29, 2000.

a Classification

G06K 9/54; G06K 9/60

(52) U.S. Cl. 382/305

(57) ABSTRACT

An improved method and device for capturing image data benefits from having a single central processor execute the operating system, and the image capture, decode and processing programs. A method for capturing of image data comprises transmitting image data from an imager, assembling the image data, assigning a memory address to the assembled image data and transferring the assembled image data into system memory. This method is capable of central processing whereby the capturing of image data is executed via the main processor without having to invoke a dedicated processor or incorporate external components, such as additional PCBs, external digital signal processing or external data storage. Additionally, an imaging device comprises an image builder module that receives image data from the imager bus and assembles the data, and a transfer controller that initiates the image builder module and controls the transfer of image data into and out of memory.



EAST Browser - L6: (122) (microcomput... | US 5048623 A | Tag: S | Doc: 9/122 (SORTED) | Format: KWIC
File Edit View Tools Window Help

US-PAT-NO: 5048623

DOCUMENT-IDENTIFIER: US 5048623 A

TITLE: Combination weighing apparatus

——— KWIC ———

Detailed Description Text - DETX (10):

The ROM 42B of the microcomputer stores a Real-time Multi-task Operating System which is shown in FIG. 5 and comprises an initialize/timer-control task "TSK1", a feeder task "TSK2", a feeding bucket task "TSK3", a weighing bucket task "TSK4", an auxiliary bucket task "TSK5" and a discharge sequence task "TSK6", respectively labeled "A", "B", "C", "D", "E" and "F" in FIG. 5.

FIG. 5



Details | Text | Image | HTML | KWIC

	U	1	Document ID	Issue Date	
8			US 4590583 A	19860520	Coin tele
9			US 5048623 A	19910917	Combinat
10			US 4868757 A	19890919	Computer

EAST Browser - L19: (32) bar near2 re... | US 5812882 A | Tag: S | Doc: 4/32 (SORTED) | Format: KWIC
File Edit View Tools Window Help

TITLE: Digital dictation system having a central station that includes component cards for interfacing to dictation stations and transcription stations and for processing and storing digitized dictation segments

——— KWIC ———

Detailed Description Text - DETX (29):

In the preferred embodiment of the present invention, the AT card 40 (FIG. 1) is a controller or a personal computer, well known to those skilled in the art, that is dedicated to running the modular digital dictation system 10 of the present invention. In the preferred embodiment, the AT card 40 is an IBM AT personal computer, specifically including a 80486 microprocessor running the OS/2 operating system. However, other microprocessors or operating systems well known to those skilled in the art may be used. The OS/2 operating system program is a multitasking system, broadly meaning that it can support many application programs running at the same time.

Detailed Description Text - DETX (135):

Other functions are performed at step 138 (FIG. 12), including creating the



FIG.4



FIG.4A

Details | Text | Image | HTML | KWIC

	U	1	Document ID	Issue Date	
3			US 6396497 B1	20020528	Computer
4			US 5812882 A	19980922	Digital dic compone transcript dictation
5			US 6353436 B1	20020305	Graphica